









Shenzhen Biocare Bio-Medical Equipment Co., Ltd.

Headquarters: 7/F, Block A, Shenzhen Mingyou Industrial Products Exhibition & Procurement Center, Baoyuan Road, Xixiang Sub-district, Bao'an District, 518102 Shenzhen, P.R. China

Factory: 2/F West, 4th Block, Dayang Road South, Fuyong Sub-district, Bao'an District, 518103 Shenzhen, P.R. China

Tel: +86-755-3661 5333 **Fax**: +86-755-2796 0643

E-mail: sales@biocare.com.cn

© 2015 BIOCARE all rights reserved. Specifications subject to changes without prior notice. ENG-CATA-V2.2-20151116












Efficiency in acquisition

- Advanced 24-bit A/D converter technology, better in weak signal detection
- · Complete filtering technology against AC, EMG interference and baseline wandering
- Individual lead wires can be exchanged
- 3 operation keys for efficiency improvement and time-saving



Freeze function

- Up to 300 seconds of uninterrupted 12-lead frozen waveforms for intermittent arrhythmia analysis.
- Selectable any 10 seconds for a fully interpreted report.

• Cabrera mode available to orientate the original position of myocardial ischemia or arrhythmia

Pacemaker detection

- Identify pacemaker types and working status through ECG analysis
- 3 status for various pacemaker types: weak, normal, enhance
- Automatically measure wave complex duration and amplitude

iE 12A

12-channel digital electrocardiograph

Data management solution

- File formats: XML, DICOM, JPG, PDF, BIOCARE private
- Internal memory can be 3000 files
- Support SD card and USB flash disk



Streamlined workflow from start to finish

- Icon buttons on the screen for intuitive operation
- Various report formats for printing







- Barcode scanner to quickly input patient ID On-screen guide to check for loose leads

Excellence in measurement and interpretation

Biocare's CardioPro™ ECG analysis program has been proven by official CSE database evaluation with high accuracy and reliability in measurement and interpretation.

Analysis for adult and pediatrics

- 0.01 Hz for high-pass filter, more sensitive in weaker ECG signal detection, contributes to undistorted ST segment measurement and analysis
- Exclusive analysis module for pediatrics with 250Hz low-pass filter, meets the latest standard of AHA/ACC/HRS 2007

Arrhythmia detection

- Auto-trigger printing when arrhythmia is detected under trigger mode
- Extending printing prompt


R-R analysis

- Up to 300 seconds R-R analysis in 1 or 3 rhythm leads for easier in arrhythmia locating
- R-R trend and histogram for clinical reference





R-R analysis





Pacemaker detection